

XP400 SUPERWASH XP-400ECO

ARTMASA STUDIO
M200307

COMEC® Italia

LAVATRICI IN ACCIAIO
INOX

INOX
STEEL WASHING
MACHINES

Le lavatrici **SUPERWASH XP-400 ECO** sono il miglior complemento alle macchine per la stampa a tampone **INKPRINT**, per la pulizia dei clichés, calamai ed altri accessori utilizzati per la stampa. Sono interamente costruite in acciaio inox e il funzionamento pneumatico garantisce una assoluta sicurezza di lavoro. La XP-400 ECO è dotata di filtro a carboni attivi con dispositivo di aspirazione prima dell'apertura della vasca. Il liquido detergente viene spruzzato all'interno della lavatrice tramite una pompa a membrana ad alta pressione e fuoriesce dagli ugelli situati sopra, sotto e ai lati del cestello, fornendo così l'energia necessaria alla rotazione dello stesso e garantendo un'ottima pulizia. Le nostre Superwash oltre al filtro a carboni attivi sono dotate di: temporizzatore pneumatico, regolatore di pressione, filtro interno per il solvente e sicurezza sull'apertura dello sportello. **A Richiesta è disponibile un distillatore per il riciclo ed il recupero del solvente di lavaggio.**

*The **SUPERWASH MODEL XP-400** washing machines are the best finishing touches for the **INKPRINT** pad printing machines for cleaning the clichés, ink-trays and other printing accessories used. They are entirely constructed in stainless steel and their pneumatic operation guarantees absolute safety on the job. The XP-400ECO is equipped with an active carbon filter with suction device that operates before the tub is opened. Liquid detergent is sprayed inside the washing machine by a high pressure membrane pump through nozzles positioned above, below and on the sides of the tub. This action supplies the energy necessary for rotating the tub and guaranteeing optimum cleaning. Our Superwash are equipped not only with the active carbon filter but also with a pneumatic timer, a pressure regulator, an internal filter for the solvent and safety device on the door opening. **A still for recycling and recovering the washing solvent is available upon request.***



SUPERWASH XP-400 ECO

w w w . c o m e c - i t a l i a . i t

SUPERWASH XP-400 ECO
Lavatrice in acciaio Inox

SUPERWASH XP-400 ECO
Inox steel washing machines



DATI TECNICI TECHNICAL DATA

Diametro cestello
Basket diameter 390 mm

Altezza cestello
Basket height 100 mm

Caricamento cestello
Basket loading Max 15 Kg

Quantità minima
richiesta liquido detergente
Minimum level required
for cleaning liquid 20 lt

Pressione alimentazione
Feeding pressure Max 3/4 atm

Peso
Weight 30 Kg

TIMER



COMEC® Italia

COMEC ITALIA SRL - Piazzale del Lavoro 149, 21044 CAVARIA (VA) ITALY
Tel. 0331/ 219516 (5 linee r.a.) Fax 0331/ 216161
www.comec-italia.it - e-mail: info@comec-italia.it

COMEC ITALIA deposito MILANO
COMEC ITALIA deposito TORINO

COMEC ITALIA deposito MANTOVA-BRESCIA
COMEC ITALIA deposito CATANIA e CAGLIARI

COMEC ITALIA deposito TREVISO
COMEC ITALIA deposito IMOLA